Portable Carbon Monoxide (CO) Monitors

Portable CO Monitor CO91-14LAC

A portable airline monitor connects easily to a breathing air filtration source or ambient air pumps and monitors the air for CO content. An audible alarm (95 dBA) and light will activate when the CO level exceeds 10 ppm (5 ppm Canadian). Used in the closed and upright position, an external alarm and lights signal the user if there are dangerous CO or CO/O_2 levels.

Portable CO and CO/O_2 Monitors

Item No.	Description
CO91-14LAC	Portable CO monitor, 150 psi maximum inlet pressure, and 5' hose
CO91-14HAC	Portable CO monitor, rated for 5000 psi maximum pressure, includes 5000 psi regulator, and 5' hose
CO2-91LAC	Portable CO/O_2 monitor, 9 VDC and/or 115 VAC, 5' hose, 150 psi maximum inlet pressure

Applications

- Filtration Systems
- Ambient Air Pumps
- Equipment Rentals
- Retrofit Portable Compressors

Portable CO Monitors - Intrinsically Safe

Item No.	Description
CO91-14IS	Portable Intrinsically Safe CO monitor, 9 VDC only, audible alarm, visual lights, flow meter, connect hose, LCD display
CO291-14IS	Portable Intrinsically Safe CO/O_2 monitor, 9 VDC only, audible alarm, visual lights, flow meter, connect hose, LCD display

Approved for Class I, Division 1, Groups C and D environments. 9 VDC operation only.

For Use In Hazardous Locations

Key Details:

- Includes ¼" industrial interchange coupling supplied on 5' hose
- Use in the closed position
- Standard alarm (95 dBA)
- High intensity alarm (120 dBA) available for an additional charge
- Standard alarm jack allows for connection to remote alarm devices
- Operates on 9-volt batteries, 8-16 VDC, or 115 VAC